

AIRPORTS DIVISION

INTERNAL AIRPORT SITES

| MEDIA TYPE | SUBSTRATE & PRINT SPECIFICATIONS |
|---|---|
| <p>Multisheets Portrait 1500mm x 1050mm</p> <p>OR Tambo Intl. Airport 1800mm x 1200mm</p> <p>Cape Town Intl. Airport</p> | <p>Yupo Material size: 1500mm x 1050mm Visual size: 1400mm x 960mm</p> <p>Material size: 1760mm x 1200mm Visual size: 1700mm x 1120mm</p> <p>Material size: 1760mm x 1200mm Visual size: 1715mm x 1130mm</p> |
| <p>International Airport sites Variable dimensions</p> | <p>Confirm with production department</p> |
| <p>Glass Panels</p> | <p>Substrate Contravision Sizes to be confirmed with production department</p> |
| <p>External Airport sites Variable dimensions Variable substrates</p> | <p>Confirm with production department</p> |

Repro Specifications:

Scans must be full colour CMYK, approx A3 at 300dpi not less than 180mb.

File Formats : Adobe Photoshop - ver3, 4, 5.5, CS3, Freehand - 8, 9, 10, 11, MX, Adobe Illustrator - 8, Corel Draw - 13, Indesign - CS3.

Convert all type to paths. Cromalin/Iris proof for colour matching purposes. May use Pantone references for spot colours, CMYK % values are not acceptable, due to differences in pigment hues from printer to printer. Bleed background to material size.

NOTES: If a document contains any scanned or raster images, supply these as separate Photoshop "tif" or "eps" files. No links should be embedded on document. Ensure document is "CMYK" not "RGB". All text must be converted to curves. Bleed must be added all round in final made up document. If no bleed is added, the file must be supplied in a layered format. All artwork must be set up to a minimum of 10% of the final size. DPI of scans should be a minimum of 300dpi and 10% of final size