

JIA 040 PANEL 1 (2/2)

ORTIA - EXTERNAL WALL SITE

A		
Panel	Height(mm)	Width(mm)
A1	970	650
A2	1100	650
A3	1100	1750
A4	1100	1750
A5	760	1750
A6	760	1750
A7	1100	1750
A8	1100	1750
A9	970	1750
A10	1400	1750
A11	1400	1750
A12	890	1750

B		
Panel	Height(mm)	Width(mm)
B1	970	1750
B2	1100	1750
B3	1100	1750
B4	1100	1750
B5	760	1750
B6	760	1750
B7	1100	1750
B8	1100	1750
B9	970	1750
B10	1400	1750
B11	1400	1750
B12	890	1750
B13	1430	1750

C		
Panel	Height(mm)	Width(mm)
C1	970	1750
C2	1100	1750
C3	1100	1750
C4	1100	1750
C5	760	1750
C6	760	1750
C7	1100	1750
C8	1100	1750
C9	970	1750
C10	1400	1750
C11	1400	1750
C12	890	1750
C13	1430	1750

D		
Panel	Height(mm)	Width(mm)
D1	970	820
D2	1100	820
D3	1100	820
D4	1100	820
D5	760	820
D6	760	820
D7	1100	820
D8	1100	820
D9	970	820
D10	1400	820
D11	1400	820
D12	890	820
D13	1430	820

Repro Specifications:

Scans must be full colour CMYK, approx A3 at 300dpi not less than 180mb.

File Formats : Adobe Photoshop - ver3, 4, 5.5, CS3, Freehand - 8, 9, 10, 11, MX, Adobe Illustrator - 8, Corel Draw - 13, Indesign - CS3.

Convert all type to paths. Cromalin/Iris proof for colour matching purposes. May use Pantone references for spot colours, CMYK % values are not acceptable, due to differences in pigment hues from printer to printer. Bleed background to material size.

NOTES: If a document contains any scanned or raster images, supply these as separate Photoshop "tif" or "eps" files. No links should be embedded on document. Ensure document is "CMYK" not "RGB". All test must be converted to curves. Bleed must be added all round in final made up document. If no bleed is added, the file must be supplied in a layered format. All artwork must be set up to a minimum of 10% of the final size. DPI of scans should be a minimum of 300dpi and 10% of final size